Geogiga Seismic Pro 11.0

Release Notes

Copyright © 2026, All rights reserved.

Table of Contents

Introduction....1

Feature Updates....2
General Updates....2
Updates to Individual Applications....5

Bug Fixes....14
Common Bug Fixes....14
Bug Fixes in Individual Applications....14

Introduction

This document provides the release notes for **Geogiga Seismic Pro ™** 11.0.

Geogiga Seismic Pro™ is a comprehensive software package for near-surface seismic data processing and interpretation. It includes 18 standalone applications, as shown in Figure 1, covering reflection, refraction, surface-wave, and borehole seismic methods, along with utilities for wavefield modeling, velocity-model plotting, and more.




Figure 1: **Seismic Pro** Launchpad with collapsible application categories

Version 11.0 is a major release featuring new functionality, enhancements, and bug fixes.

Key updates include automatic layer assignment for refraction interpretation, surface-wave backscatter analysis, integrated Vp-based dispersion inversion, conversion of SRT velocity models to layered models, powerline interference suppression, and enhanced microtremor analysis.

All applications are now 64-bit, removing practical data-size limitations for large 2D and 3D SRT surveys, long reflection lines, and long-duration passive surface-wave recordings.

These release notes are organized into two sections: **Feature Updates** and **Bug Fixes**.

Feature Updates

This section summarizes general enhancements to **Seismic Pro** 11.0, followed by updates to individual applications.

General Updates

The following enhancements apply to most **Seismic Pro** applications:

- **64-bit applications** – Upgraded all applications from 32-bit to 64-bit to support larger datasets and longer recordings.
- **File commands** – Consolidated the **New** and **Open** commands into a single **Open** command with three options. See Figure 2.




Figure 2: Open command options

- **Recent Files** – Added a menu for reopening previously accessed files.
- **Trigger delay** – Applied consistently to trace display, first-arrival picking, trace muting for dispersion analysis, velocity analysis, and related operations.
- **First-arrival picking** – Improved drag picking with automatic snapping, added continuous picking across traces, and added a help overlay to the trace view. See Figure 3.




Figure 3: First-arrival picking with automatic snapping

- **Merged seismic file editing** – Added options to remove, replace, insert, or append individual records in merged seismic files. See Figure 4.




Figure 4: Editing records in a merged seismic file

- **Trace display** – Added **−**, **0**, and **+** buttons beside the horizontal scrollbar, along with **Alt + Left/Right Arrow** keyboard shortcuts for adjusting display gain.
- **2D section display** – Added options to set the X-axis range and reverse the vertical colorbar. Added automatic saving and loading of display settings, and improved blanking file generation when exporting 2D sections.
- **3D views** – Added help overlays to the 3D and 3D Fence views, along with automatic saving and loading of display settings.
- **Curve axes** – Added automatic scientific notation for X- and Y-axis labels when displaying very large or very small values.
- **Shot point coordinates** – Preserved shot point coordinates when applying the current record geometry to all records.
- **SEG-2 keyword handling** – Improved support for user-defined keywords.
- **Windows dialogs** – Switched file open/save, font, and color dialogs to the Windows API to improve compatibility with third-party software.
- **Help menu** – Added the **General Features Guide** command to the **Help** menu in each application.

Updates to Individual Applications

The following updates apply to individual **Seismic Pro** applications:

Front End

- Improved interactive trigger-time correction based on direct-wave or air-wave velocity. See Figure 5.




Figure 5: Interactive trigger-time correction based on air-wave velocity

- Added an option to set the trace-header delay (pre-trigger) value for selected files.
- Added a function to calculate and save differences between two seismic data files.
- Added an option to test apparent velocity.
- Added support for flexible file-table formats when assembling nodal seismic traces.
- Added file selection with the **Up/Down Arrow** keys and loading with **Enter**.
- Added support for saving geometry information from a single seismic file to a text file.
- Added a **Clear Recent Directories** command to the directory drop-down list.

SeisMapper

- Increased the maximum number of horizontal samples to support longer profiles.

Reflector

- Added tomographic static correction for crooked lines using a 2D velocity model exported from **DW Tomo**. See Figure 6.




Figure 6: Tomographic static correction for crooked lines

- Added an option to set the maximum frequency for F-K filter plots.
- Added support for resizing the F-K and Tau-p filter views.

Refractor

- Added automatic layer assignment. See Figure 7.




Figure 7: Automatic layer assignment (left: before; right: after)

- Added reduced-traveltime TX curve plots to help verify and adjust layer assignments. See Figure 8.




Figure 8: TX curve plots (left: standard; right: reduced traveltime)

- Added powerline interference suppression.

DW Tomo

- Added powerline interference suppression. See Figure 9.




Figure 9: Powerline interference suppression (left: before; right: after)

- Improved building of initial velocity models and setting of tomography velocity limits.
- Added conversion of SRT models to layered models, with the number of layers and layer velocities determined automatically. See Figure 10.




Figure 10: Layered model conversion (left: SRT model; right: layered model)

DW Tomo3D

- Added trigger-time correction.
- Improved building of initial velocity models and setting of tomography velocity limits.

Surface and Surface Plus

- Added support for building initial inversion models using Vp imported from **Refractor**, **DW Tomo**, or **Reflector** results, enabling a more integrated workflow across active and passive MASW, SRT, and conventional refraction and reflection methods.
- Added an option to set the search range, Poisson's ratio, and density to uniform values for the initial models of all dispersion curves.
- Improved the initial Vs model used for inversion when re-iteration is enabled.
- Set the default A value for SPT-N calculations based on the selected measurement units (meters or feet).
- Added calculation of elastic moduli, including shear modulus (Gmax), Young's modulus, and bulk modulus.
- Added simultaneous display of velocity and derived property sections. See Figure 11.




Figure 11: Simultaneous display of Vs, Vp, Poisson's ratio, and shear modulus sections

- Added muting for mid-shot records. See Figure 12.




Figure 12: Mid-shot muting

- Added options to customize the color and line width of the dispersion-curve picking search box, along with a help overlay.

Surface Plus only

- Extended CMZ gather generation to 3D active or passive surface-wave surveys. See Figure 13.




Figure 13: CMZ gather generation for 3D surveys

- Added backscatter analysis of surface waves (BASW). See Figure 14.




Figure 14: Seismic data (above) and BASW section (below)

Microtremor

- Replaced the **Open** button with an integrated file list for loading data.
- Added automatic rejection of noisy time windows.
- Added Konno–Ohmachi smoothing and options to combine horizontal components using RMS or the geometric mean.
- Added automatic peak detection, result evaluation, and detailed result displays.
- Added mean, upper, and lower HVSR curves, with estimates of F_0, σ_F, A_0, and σ_A. See Figure 15.




Figure 15: HVSR curves and peak estimates

- Added options to customize curve displays and export HVSR curves.
- Added conversion of SAF data files to SEG-2 format.

XW Tomo

- Added powerline interference suppression.

VSP

- Changed pick deletion from **Ctrl+left-click** to **right-click** and added a help overlay.

PS Log

- Changed pick deletion from **Ctrl+left-click** to **right-click** and added a help overlay.
- Added conversion from ft/s to m/s for modulus calculations.
- Changed the units of shear, Young's, and bulk moduli from GPa to MPa.

Bug Fixes

This section summarizes common bug fixes in **Seismic Pro** 11.0, followed by fixes specific to individual applications.

Common Bug Fixes

The following fixes apply to most **Seismic Pro** applications:

- Fixed single-trace display to center the trace in the display window.
- Fixed the enabled/disabled states of **All Records** and **Current Record** in the first-arrival picking view to reflect the number of records displayed.
- Fixed truncation of vertical colorbar labels in 2D section displays when changing the font size.
- Fixed crashes when opening or saving files on some computers due to conflicts with third-party software.

Bug Fixes in Individual Applications

The following fixes apply to individual **Seismic Pro** applications:

Front End

- Fixed an issue where the selected component was ignored when assembling three-component nodal seismic records and saving them in SEG-2 format.

SeisMapper

- Fixed an issue where the start and end coordinates became editable when selecting 2D sections.

Modeling2D

- Fixed an issue that prevented saving seismograms with more than 64K samples.

Reflector

- Fixed missing CMP coordinate assignments for straight survey lines in the **CMP Binning** dialog box.
- Fixed incorrect trace order in frequency-spectrum plots when seismic coordinates decreased along the survey line.

SF Imager

- Fixed an issue where imported velocity-profile locations were always set to 0 and could not be changed.

Refractor

- Fixed an issue where first-arrival picking in the **Trace Magnifier** window did not work for some shot records.
- Corrected receiver plotting to use downward-pointing arrows.
- Corrected plotting of shot points and receivers along non-flat survey lines.

DW Tomo

- Fixed an issue where a node was incorrectly added when the mouse cursor moved outside the time-offset plot while adjusting the initial velocity profile.
- Corrected receiver plotting to use downward-pointing arrows.

Surface and Surface Plus

- Fixed an issue where elevation was not included in apparent-velocity calculations.
- Fixed an issue that reset the starting display frequency of dispersion images to zero when selecting a different record.
- Fixed incorrect dispersion curve locations when loading certain files saved in versions earlier than V10.0.

Surface Plus only

- Fixed incorrect default geophone spacing value calculated from common-zone gathers instead of common-shot gathers.
- Fixed an issue that incorrectly enabled the **Save** and **Save As** commands when common-zone gathers were plotted.
- Fixed an incorrect default frequency range when combining spectra from multiple records for some seismic data.

XW Tomo

- Fixed a crash when automatically extending the velocity model to include all sources and receivers for certain geometry configurations.